

# AGC-40 CA PRODUCT SPEC SHEET

AGC-40 CA

**COCONUT SHELL CARBON** 

**PREMIUM GRADE ACID-WASHED SEMI MOIST COCONUT SHELL CARBON COARSE MESH (12X40)** 

ResinTech AGC-40 CA is a semi moist 12 x 40 mesh coconut shell based granular activated carbon. It is dust free and acid washed to neutralize pH and conductivity when first placed into use. ResinTech AGC-40 CA is intended for chlorine or NOM removal where rapid adsorption is required. It is Gold Seal Certified by the WQA for use in potable water applications.

#### **APPLICATIONS**

- Chlorine Reduction
- Organics Reduction



TYPICAL PROPERTIES & PHYSICAL CHARACTERISTICS	
Physical Form	Carbonaceous Granules
Particle Size	12 to 40 US Mesh (400 - 1680 μm)
% < 50 mesh (300μm)	< 5%
Temp Limit	212°F (100°C)
Moisture Retention	20% to 30%
Shipping Weight	37 - 39 lbs/ft³ (593 - 625 g/L)
Color	Black
Uniform Particle Size	Yes

# **PACKAGING OPTIONS**

- 1 ft<sup>3</sup> bags
- 1 ft<sup>3</sup> drums
- 1 ft³ boxes • 7 ft<sup>3</sup> drums
  - 42 ft<sup>3</sup> supersacks

### **CERTIFICATIONS**

- WQA Gold Seal\*
- Kosher Certified

## SUGGESTED OPERATING CONDITIONS

Maximum continuous temperature 250°F Minimum bed depth Chlorine removal 24 inches Chloramine removal 36 inches Support bed 12 inches Backwash expansion 15 to 25 percent 6 to 10 gpm/sq.ft. Backwash flow rate Service flow rate 1 to 5 gpm/cu.ft. Chlorine removal Chloramine removal 0.5 to 1.0 gpm/cu.ft.

Note: These guidelines describe average low risk operating conditions. They are not intended to be absolute minimums or maximums.

For operation outside these guidelines, contact ResinTech Technical Support

Revision 1.4 ResinTech, Inc.®



<sup>\*</sup> NSF/ANSI/CAN 61: Drinking Water System Components - Health Effects